

DR-75W单组输出导轨电源 DR-75W Single output DIN rail power supply

概述 Summary

- > 单组输出：功率75W
Single output: power 75W
- > 输入电压：85 ~ 264VAC 120 ~ 370VDC
Input voltage: 85 ~ 264VAC 120 ~ 370VDC



常见规格 General Specification

55.5 × 125.2 × 100mm

性能 Specification	型号 Model	DR-75-12	DR-75-15	DR-75-24	DR-75-48
直流输出电压、电流 DC output voltage, current		12V 0~6.3A	15V 0~5A	24V 0~3.2A	48V 0~1.6A
纹波及噪音 Wave and noise		100mVp-p	150mVp-p	150mVp-p	240mVp-p
进线稳定度 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability		±0.5%	±0.5%	±0.5%	±0.5%
效率 Efficiency		76%	80%	80%	81%
直流电压可调范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%
输入电压范围 Input voltage range		85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz			
冲击电流 Impact current		冷启动电流 Cold start current 20A/115VAC 40A/230VAC			
过载保护 Overload protection		105% ~ 150%切断输出，自动恢复 105% ~ 150% cut off the output, automatic recovery			
过电压保护 Over voltage protection		121% ~ 142%关闭输出，电源重启后可恢复输出 121% ~ 142% shut down O/P voltage, re-power on to recover			
启动、上升、保持时间 Setup, rise, hold up time		1000ms, 60ms, 60ms/230VAC 满负载 at full load			
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C ~ +50°C			
尺寸 Dimension		55.5 × 125.2 × 100mm			
重量 Weight		0.55kg			
包装 Packing		42 × 25 × 24CM/24PCS/13.5kg			

外形尺寸 Overall dimension(mm)

接线位置

- ☒ 端口 1,2 : 交流输入
- ☒ 端口 3 : 接地
- ☒ 端口 4,5 : 直流输出-V
- ☒ 端口 6,7 : 直流输出+V

Terminal Pin No. Assignment

- ☒ Pin 1,2 : AC input
- ☒ Pin 3 : GND
- ☒ Pin 4,5 : DC output-V
- ☒ Pin 6,7 : DC output+V

